

We use cookies to ensure that we give you the best experience on our website. By continuing, we assume that you accept such use.



Accept

Decline

Website: www.pelonistechologies.com

DC Cross Flow Fan JSD-030A Series

145mm (5.7in) to 347mm (13.7in) lengths. DC Brushless type motor, temperature resistant aluminum alloy, ball or sleeve bearings. Maximum Pressure: 1.5mmAq (0.059inH₂O) to 1.9mmAq (0.074inH₂O), Maximum Air Flow: 21CFM (0.6m³/min) to 49CFM (1.3m³/min). CE, UL listed.



1

Model Number	Shipping Weight	Fan Type	Length A	Length B	Length C	Rated Voltage	Rated Current	Speed	Maximum Pressure	Maximum Air Flow	CFM	Noise	Weight
JSD-03009A12	160 g	DC Fan	98 mm	132 mm	145 mm	12 V	0.15 A	3200 rpm	1.9 mmAq	0.6 m ³ /min	21	29 dBA	0.160 kg
JSD-03009A24	160 g	DC Fan	98 mm	132 mm	145 mm	24 V	0.15 A	3200 rpm	1.9 mmAq	0.6 m ³ /min	21	29 dBA	0.160 kg
JSD-03015A12	190 g	DC Fan	160 mm	194 mm	207 mm	12 V	0.18 A	3100 rpm	1.7 mmAq	0.8 m ³ /min	28	30 dBA	0.190 kg
JSD-03015A24	190 g	DC Fan	160 mm	194 mm	207 mm	24 V	0.16 A	3100 rpm	1.7 mmAq	0.8 m ³ /min	28	30 dBA	0.190 kg
JSD-03019A12	210 g	DC Fan	198 mm	232 mm	245 mm	12 V	0.20 A	2900 rpm	1.6 mmAq	1.0 m ³ /min	35	31 dBA	0.210 kg
JSD-03019A24	210 g	DC Fan	198 mm	232 mm	245 mm	24 V	0.16 A	2900 rpm	1.6 mmAq	1.0 m ³ /min	35	31 dBA	0.210 kg
JSD-03029A12	290 g	DC Fan	300 mm	334 mm	347 mm	12 V	0.22 A	2600 rpm	1.5 mmAq	1.3 m ³ /min	49	33 dBA	0.290 kg
JSD-03029A24	290 g	DC Fan	300 mm	334 mm	347 mm	24 V	0.20 A	2600 rpm	1.5 mmAq	1.3 m ³ /min	49	33 dBA	0.290 kg

1